AUTOMOTIVE SPECIALTY TOOLS **TAILLIGHT REMOVAL TOOL SET**





Speedy and no damage to remove the taillight!

Shorten the work time and comfort bulb replacement work by the force of the suction cups to pull and remove the pin-clipped taillight unit.

Available for various types of taillight



Easily remove taillight by using plural removers without damaging the body.

Adjust adsorption strongness by changing the number of suction cups



You can remove small taillight certainly by using additional suction cups.



TAILLIGHT REMOVAL TOOL SET

TAILLIGHT REMOVAL	(W350×D305×H84)		
No.ATP7014	▼kg 1.6	₫5	MSRP ¥ 14,000
Taillight remover $\times 2$			AP701
2-piece set of suction cup for	ece set of suction cup for taillight remover		
Plastic case			

[Features]

•The force of the suction cups remove the pin-clipped taillight unit.

·Various taillights can be applicable by using two removers


•The resin grip gives comfortable fitting and avoid slipping.

+2 deep suction cups firmly adhere to curved surfaces. Suction cups moves flexible and slidable.

•2 additional suction cups included. You can use them for increasing

adsorption force or its replacement. With plastic case

*Plastic case is not sold individually



AP701-1



With plastic case

Provide solutions for removing the taillight!

·If you try to remove it with a hard tool, it will scratch the car body.

 It takes time to cover the car body for preventing scratches.



Solution

Reduce the working time with suction cups without damaging and covering the car body!



Spare part

No.	Description	▼g	G	MSRP
AP701	TAILLIGHT REMOVER	188	1	¥ 7,000
AP701-1	2-PIECE SET OF SUCTION CUP FOR TAILLIGHT REMOVER	13	1	¥ 1,400

*Plastic case is not sold individually

Speedy disassembling & assembling without damaging the lens and housing!

Reduce the working time and risks of headlight breakage even if you work alone.

Disassembly of headlight lens

The remover and wedge pull apart headlight lens and housing, and secure a work space.



The remover is easy to insert the space between headlight and housing, and does not slip when it pulled apart. The wedge keep the space between headlight and housing.

Assembly of headlight lens

Easy to insert gasket into the housing with the spatula.



Gasket can be inserted into the housing smoothly with the silicon spatula.

Any shape of taillights are applicable

with strong adsorption.

Handle shape and size are easy to grip with one hand and both hands.



Additional and spare suction cups are available. Suction cups moves flexible and slidable.

Suction cups are deep for strong adsorption, and big enough to disassemble of taillight. They fit various taillight. (Suction cup diameter 55mm)



AP701

Headlight lens gasket spatula



AP701-1





Headlight lens wedge $\times 2$

Headlight lens remover

HEADLIGHT LENS REPLACEMENT TOOL SET

No.ATP6015	▼g 850	10 ⊡	MSRP ¥ 14,000
Headlight lens remover		AP601	
Headlight lens wedge ×2		AP602	
Headlight lens gasket spatula		AP603	
Case			

[Purpose]

•Replacement of automobile headlamp lenses. (only for the vehicles specified by car manufacturers can be replaced)

[Features]

•Reduce working time to replace (disassemble/assemble) headlight lenses. [Headlight lens remover]

•The tip opens when gripped, and the unique shape of the claw tip keeps the space without slipping.

[Headlight lens wedge]

•Keep a work space with vertical and horizontal burrs. [Headlight lens gasket spatula]

•Gasket can be inserted into the housing smoothly with the silicon spatula.

KTC KYOTO TOOL CO., LTD.

128 Sayama-Shinkaichi, Kumiyama-cho Kuse-gun, Kyoto 613-0034, Japan Contact: contact@kyototool.co.jp Official site: en.ktc.jp

•All sizes on this leaflet are indicated as millimeter unless mentioned.

•There might be size differences between those mentioned on this leaflet and the actual products but they are under our specification.

Product design might be changed for the improvement.

