

# RECHARGEABLE LED CLAMP LIGHT



Fixed by magnet attachment



Fixed by clamping

## Magnetic, Clamp, and Placeable Work Lights. Adaptable to Various Work Environments

With adjustable angles in all directions and four brightness levels, this work light illuminates work areas during automobile inspections, maintenance, or tasks in warehouses and outdoor environments, especially in dark or nighttime conditions. Maximum brightness of 1,600 lm for powerful illumination.



### Freely adjust the angle for precise illumination

The angle can be adjusted in 8 stages vertically (250 degrees) and continuously (280 degrees) horizontally.

### Fixed to thin round bars



Fixed in place by clamping it where magnets cannot be used.

### Easy-to-see indicators



The charging indicator lets you know the battery status while in use or charging.

- Brightness **1600** lm
- Battery **3.0** hours
- 4** dimming levels
- USB Type-C

No.AL812L


### RECHARGEABLE LED CLAMP LIGHT

No.	Light source (lm)	Continuous use time (h)	Weight (g)	□
AL812L	1,600 <Strong>	3.0 <Strong>	630	1

- The LED light part can be raised from the main body and the angle can be adjusted up, down, left and right.
- The built-in magnet on the back of the product allows it to be attached to a metal surface.
- In environments where magnets cannot be used, it can be fixed with a clamp.
- Clampable size: thickness 1 to 70 mm
- Dimming level: 4 levels (strong, medium, weak, eco)
- Brightness (continuous use time): 1,600lm <strong> (3 hours), 700lm <medium> (5 hours), 300lm <weak> (8 hours), 100lm <eco> (24 hours)\* (See note)
- Charging port: USB Type C, charging time is approximately 3.5 hours
- Dustproof and waterproof: IP65
- Using environment temperature: 5-35°C
- Accessories: USB charging cable (charger not included)

\*The above specifications may vary depending on the battery condition and the charging environment.

- CAUTION**
- Do not shine the LED light directly into your eyes.
- Do not use with wet hands.
- Do not use underwater or in the rain.
- Do not place near electronic devices or other items or places that are affected by magnetism.
- Cannot be charged with a quick charger. (Recommended charger conditions: 5V 2A)
- Charge using the included charging cable.



## KTC KYOTO TOOL CO., LTD.

128 Sayama-Shinkaichi, Kumiyama Kuse-gun, Kyoto 613-0034, Japan

Official site: en.ktc.jp

- All sizes on this leaflet are indicated as millimeter unless mentioned.
- There might be size differences between those mentioned on this leaflet and the actual products for the product tolerance.
- Product design might be changed for the improvement without the notifications.

