

FILTER OIL CATCHER



[Applicable Engine Models (Examples)]

R06A

Suzuki Alto, Wagon R, Jimny, etc.

PE-VPR

Mazda MAZDA6, etc.

EJ20

Subaru WRX, Forester, etc.

Designed for Removing 67mm-14 Flute Short Oil Filters!

A 67mm-14pt. dedicated type has joined the Filter Oil Catcher lineup! It enables removal of short-type oil filters without interfering with surrounding components. Prevents oil leakage from the filter connection and keeps hands clean for efficient operation.



No.AVP-067

Issue

Some vehicle models use short oil filters in both 64mm and 67mm sizes. Without checking the actual vehicle, it is difficult to determine the correct size, causing workflow inefficiencies.

Solution

Added support for 67mm-14pt. short oil filters!

When used together with the existing 64mm-14pt. model (AVP-6364), work will not be interrupted regardless of filter size.

The new model adopts an orange color for easy identification from the existing yellow model, helping prevent hand contamination and improving work efficiency.

FILTER OIL CATCHER

No.	L	D	Weight(g)	□
AVP-067	105	88	50	1

- Dedicated tool for removing downward-facing oil filters.
- Compatible with 67mm-14pt. oil filters.
- Compact size allows removal of short oil filters.
- Enables clean oil filter removal without dirtying hands, reducing cleanup time and improving efficiency.
- Lightweight, oil-resistant resin construction. Orange color for easy identification from No. AVP-6364 series.

* This product is NOT an oil filter wrench. Use an oil filter wrench for loosening operations.

67mm-14pt. (downward)

64mm-14pt. (downward)

Applicable Oil Filters



AVP-067

With both sizes, you're fully covered.




AVP-6364

See back page for details.



67mm-14pt. (downward)



Improve Oil Filter Replacement Efficiency!

Loosen
with an oil filter wrench



CUP TYPE OIL FILTER WRENCH
No.AVSA14A

Replace oil filters
without getting your hands dirty



FILTER OIL CATCHER
No.AVP-067
See front page for details.

Prevent oil leakage
with a torque wrench



3/8"sq. TORQUE WRENCH
PRE-SET TYPE
No.GW050-03

Web catalogue



14-piece Oil Filter Wrench Set From 63mm to cartridge-type oil filter wrenches

3/8" SQ. 14 PCS.



Search compatible filter wrenches for Japanese and imported vehicles!
Applicable Oil Filters



CUP TYPE OIL FILTER WRENCH SET [14pcs.]

No.	Weight (kg)
AVSA14A	4.1
Set contents	
Cup-Type Oil Filter Wrench	AVSA-063,064,067,073,074,075D,079,080,089,A92,099,101
Cartridge-Type Oil Filter Wrench	AVSA-R64A2,R64B2
Case (W550×D380×H115)	

- Used for removing and installing automotive oil filters.
- Compatible with all oil filters used in Japanese vehicles sold since 2005.
- * As of September 2024
(Also supports rare vehicles using special-shaped oil filters.)
- With this set, quick and reliable oil filter replacement is possible regardless of the vehicle.
- Comes with a newly designed blow-molded resin case. Lightweight, durable, and scratch-resistant for easy transport.

For Removing 63mm and 64mm-14pt. Downward Oil Filters in Tight Spaces!




Web catalogue



FILTER OIL CATCHER

No.	L	D	Weight (g)	☞
AVP-6364	105	80	50	1

- Dedicated tool for removing downward-facing oil filters.
- Multi-step cup design supports 63mm and 64mm-14pt. oil filters.
- Compact size enables removal of short oil filters.
- Prevents hand contamination and improves efficiency.
- Lightweight, oil-resistant material with reduced visibility of stains.
- * This product is NOT an oil filter wrench.
Use an oil filter wrench for loosening operations.



For Removing the 4 Major Sizes of Downward Oil Filters!




Web catalogue



FILTER OIL CATCHER

No.	L	D1	D2	Weight (g)	☞
AVP-6376	178	90	62	64	1

- Used for removing downward-installed oil filters after loosening.
- Prevents hand contamination compared to conventional removal by bare hands or rubber gloves.
- Made of polypropylene for lightweight and excellent oil resistance.
- Multi-step cup design supports the 4 major sizes of downward oil filters.
- * This product is NOT an oil filter wrench.
Use an oil filter wrench for loosening operations.



Oil filter wrench application table

Outer diameter	Number of edges	Applicable engine examples
63mm (64mm)	14 pt.	R06A, K6A etc.
64mm (65mm)		R06A, 1NZ-FXE, HR12DE etc.
67mm (68mm)		EJ20, PE-VPR etc.
76mm (76mm)	15 pt.	SH-VPTS, S5-DPTS etc.

* Values in parentheses indicate outer diameter notation used by other manufacturers.

KTC KYOTO TOOL CO., LTD.

128 Sayama-Shinkaichi, Kumiya Kuse-gun, Kyoto 613-0034, Japan

Official site: en.ktc.jp

- All sizes on this leaflet are indicated as millimeter unless mentioned.
- There might be size differences between those mentioned on this leaflet and the actual products for the product tolerance.
- Product design might be changed for the improvement without the notifications.

